



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 12/1/2016

## DAP® PATCH-N-PAINT® Lightweight Spackling Nail Hole Filler

- Patch & prime in one step
- Fast drying – 30 minute Paint Ready
- No sanding
- Won't shrink/crack
- Interior/exterior
- Low odor

**Packaging:** 2.8 fl. oz (82 mL)  
**Color:** Off White  
**UPC Number:** 7079812315

### Company Identification:

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224  
**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"  
**Order Information:** 800-327-3339  
**Fax Number:** 410-558-1068  
Also, visit the DAP website at [dap.com](http://dap.com)

### Product Description:

DAP® PATCH-N-PAINT® Lightweight Spackling Nail Hole Filler offers a quick and easy method of patching interior surfaces. Fill nail holes, minor dents or cracks in walls, ceilings or woodwork prior to painting or wallpapering. It dries in minutes, does not require sanding and won't crack or shrink.

### Suggested Uses:

- Ideal for filling nail holes and small dents.
- Excellent for ceiling applications.

### Surface Preparation & Application:

- Surface must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
- Remove top, grip tube bottom, and "twist up" small amount (about 1/16") of spackling patch.
- Either apply directly to surface, or using spackling knife provided in the cap, scrape off spackling patch from top of tube and apply to wall.
- Dries in minutes, won't crack or shrink.
- Paint in minutes with latex paint. To paint with oil-based paint, allow to dry thoroughly. Patch-N-Paint Lightweight Spackling Nail Hole Filler typically dries in approximately 3 hours depending on relative humidity and depth of fill.

**Typical Physical & Chemical Characteristics:**

Consistency:	Thick Paste
Vehicle:	Latex Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Mild
Weight/gallon:	3.4
Volume Solids:	75% by volume
Shelf Life:	9 Months Minimum
Freeze/Thaw Stability:	3 Cycles @ 0°F
Temperature Service Range:	0°F to 160°F
Application Temperature	40°F Minimum
SDS No:	000 7715 0001

**Clean Up:**

Clean up immediately after use with soap and water. Be sure container is sealed tightly. Store in a cool dry place. Dry material must be cut, scraped or sanded away.

**Safety:**

See product label and Safety Data Sheet (SDS) for additional information. For an SDS contact your supplier or visit dap.com.

**Warranty:**

If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.