



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® All Purpose Stucco Patch (Ready Mix)

### PRODUCT DESCRIPTION

DAP® All-Purpose Stucco Patch may be used to repair small holes and cracks in interior and exterior stucco surfaces. It's ready to use sanded formula blends naturally with existing stucco for a professional finish.



PACKAGING	COLOR	UPC
Quart	White	7079810504
Gallon	White	7079860590

### KEY FEATURES & BENEFITS

- For repairing small holes and cracks in stucco surfaces
- Durable and permanent
- Textured finish
- Ready to use
- Easy to tool and paint
- Interior/exterior use

### SUGGESTED USES

For patching small holes and cracks in stucco surfaces.

### FOR BEST RESULTS

- Consult paint manufacturer's recommendations before decorating. To repair large breaks, cracks and holes in stucco surfaces, use DAP Stucco Patch Dry Mix.
- Can be painted after final cure (3 days).
- **DO NOT USE AS A SKIM COAT.**



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## APPLICATION

1. Surface must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
2. Apply stucco patch with a clean putty knife or trowel. For fills over 1/4" deep, apply 2 or more layers allowing each layer to dry before applying the next one.
3. Use a rubber float to blend patch with the existing stucco surface.
4. Store the tightly sealed container in a cool, dry place for re-use.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Setting Time:	2 to 4 hours
Final Cure:	3 Days
Odor:	Mild
Consistency:	Coarse, thick paste
Vehicle:	Latex emulsion
Volatile:	Water
Filler:	Calcium carbonate, sand
Solids:	84 ± 1.0% by weight
Weight per Gallon:	15.6 lbs./gal.
Shelf Life:	12 months
Coverage:	1 qt./946 mL 12-18 sq. ft.
	1 gal. 48-72 sq. ft. NOTE: These figures are approximate and may vary with job site conditions

## CLEAN UP & STORAGE

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## WARRANTY

### **Limited Warranty:**

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**